



## OUTBOARD MOTOR OIL

000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : OUTBOARD MOTOR OIL  
Product code : POMDRM, POMC24, POMC16, POMC12, POM, POMBLK

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Ashless 2-cycle engine oil designed to lubricate water-cooled two-cycle engines. For use where TC-W3(R) oils are recommended.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details  
Petro-Canada Europe Lubricants Limited  
Wellington House, Starley Way  
Birmingham International Park Solihull B37 7HB  
United Kingdom  
E-mail address of person responsible for the SDS : EUSDS@petrocanadalsp.com

#### 1.4 Emergency telephone number

Emergency telephone number : Petro-Canada Lubricants Inc.: +1 905-403-5770;  
CHEMTREC Transport Emergency: 1-800-424-9300;  
Poison Control Centre: Consult local telephone directory for emergency number(s).

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**  
Not a hazardous substance or mixture.

#### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008)**  
Not a hazardous substance or mixture.

#### **Additional Labelling:**

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

None known.



## OUTBOARD MOTOR OIL

000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
distillates (petroleum), hydrotreated light paraffinic	64742-55-8 265-158-7 01-2119487077-29-0036	Asp. Tox. 1; H304	30 - 50
distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-0055	Asp. Tox. 1; H304	20 - 30
Highly refined mineral oil		Asp. Tox. 1; H304	1 - 10

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary.  
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Wash clothing before reuse.  
Seek medical advice.
- In case of eye contact : Remove contact lenses.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Obtain medical attention.
- If swallowed : Rinse mouth with water.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.  
Seek medical advice.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : First aider needs to protect himself.

## OUTBOARD MOTOR OIL

000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

### 4.3 Indication of any immediate medical attention and special treatment needed

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : No information available.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.

Hazardous combustion products : Carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO<sub>x</sub>), sulphur oxides (SO<sub>x</sub>), aldehydes, hydrocarbons, smoke and irritating vapours as products of incomplete combustion.

### 5.3 Advice for firefighters

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.  
Material can create slippery conditions.  
Mark the contaminated area with signs and prevent access to unauthorized personnel.  
Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.

### 6.4 Reference to other sections

For personal protection see section 8.



## OUTBOARD MOTOR OIL

000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Use only with adequate ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Do not ingest.  
Keep away from heat and sources of ignition.  
Keep container closed when not in use.
- Advice on protection against fire and explosion : None known.
- Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

#### 7.3 Specific end use(s)

---

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### 8.2 Exposure controls

##### Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

##### Personal protective equipment

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.



## OUTBOARD MOTOR OIL

000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Filter type : organic vapour
- Protective measures : Wash contaminated clothing before re-use.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

- Appearance : viscous liquid
- Colour : blue green
- Odour : Hydrocarbon.
- Odour Threshold : No data available
- pH : No data available
- Pour point : -48 °C (-54 °F)
- Boiling point/boiling range : No data available
- Flash point : 134 °C (273 °F)  
Method: Pensky-Martens closed cup
- Fire Point : 170 °C (338 °F)
- Auto-Ignition Temperature : No data available
- Evaporation rate : No data available
- Flammability (solid, gas) : Low fire hazard. This material must be heated before ignition will occur.
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available



## OUTBOARD MOTOR OIL

000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

Relative density	:	No data available
Density	:	0.868 kg/l (15 °C / 59 °F)
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity	:	
Viscosity, kinematic	:	55.6 cSt (40 °C / 104 °F)
		8.8 cSt (100 °C / 212 °F)
Explosive properties	:	Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

### 9.2 Other information

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

### 10.2 Chemical stability

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
---------------------	---	---

### 10.4 Conditions to avoid

Conditions to avoid	:	No data available
---------------------	---	-------------------

### 10.5 Incompatible materials

Materials to avoid	:	Reactive with oxidising agents, reducing agents and acids.
--------------------	---	--

### 10.6 Hazardous decomposition products

Hazardous decomposition products	:	May release CO <sub>x</sub> , SO <sub>x</sub> , hydrocarbons, methacrylate monomers, asphyxiants, smoke and irritating vapours when heated to decomposition.
----------------------------------	---	--

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure	:	Eye contact Ingestion Inhalation Skin contact
--	---	--



## OUTBOARD MOTOR OIL

000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

### Acute toxicity

#### Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

#### Components:

##### **distillates (petroleum), hydrotreated light paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

### Skin corrosion/irritation

#### Product:

Remarks : No data available

### Serious eye damage/eye irritation

#### Product:

Remarks : No data available

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available



## OUTBOARD MOTOR OIL

000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

#### 12.2 Persistence and degradability

**Product:**

Biodegradability : Remarks: No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

Not relevant

#### 12.6 Other adverse effects

No data available

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

---

### SECTION 14: Transport information

#### International Regulations

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)

™ Owned or used under license.





## OUTBOARD MOTOR OIL

000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

Remarks : ADR: Not Regulated  
ADN: Not Regulated  
RID: Not Regulated

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class : WGK 1 slightly water endangering  
(Germany)

#### The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EINECS : On the inventory, or in compliance with the inventory

#### 15.2 Chemical safety assessment

---

### SECTION 16: Other information

#### Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

#### Full text of other abbreviations

Asp. Tox. : Aspiration hazard

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## OUTBOARD MOTOR OIL



000003000691

Version 2.0

Revision Date 2018/09/25

Print Date 2018/09/25

Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

For Copy of SDS : Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)  
Europe, telephone: 00-800-7387-6000  
For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG\_EU / EN